MUS-TDL-ON-85-2

U.S. DEPARTMENT OF COMMERCE NATIONAL OCEANIC AND ATMOSPHERIC ADMINISTRATION NATIONAL WEATHER SERVICE OFFICE OF SYSTEMS DEVELOPMENT TECHNIQUES DEVELOPMENT LABORATORY

COLLAND IN 62225

TDL OFFICE NOTE 85-2

11 FEB 1985

AFOS-ERA VERIFICATION OF GUIDANCE AND LOCAL AVIATION/PUBLIC WEATHER FORECASTS--NO. 2
(APRIL 1984-SEPTEMBER 1984)

Gary M. Carter, Valery J. Dagostaro, J. Paul Dallavalle, Normalee S. Foat, J. Todd Hawes, George W. Hollenbaugh, and George J. Maglaras

AFOS-ERA VERIFICATION OF GUIDANCE AND LOCAL AVIATION/PUBLIC WEATHER FORECASTS--NO. 2 (APRIL 1984-SEPTEMBER 1984)

Gary M. Carter, Valery J. Dagostaro, J. Paul Dallavalle, Normalee S. Foat, J. Todd Hawes, George W. Hollenbaugh, and George J. Maglaras

1. INTRODUCTION

This is the second in a new series of Techniques Development Laboratory (TDL) office notes which compare the performance of TDL's automated guidance with National Weather Service (NWS) local forecasts made at Weather Service Forecast Offices (WSFO's). All of the forecasts (both local and guidance) and the verifying observations were collected locally at the WSFO's, transmitted via the Automation of Field Operations and Services (AFOS) system to the National Meteorological Center, and archived centrally by TDL. The local collection system is described by Miller et al. (1984), while guidelines for the public/aviation forecast verification program are given in National Weather Service (1983a).

In this report, we present verification statistics for the warm season months of April through September 1984 for probability of precipitation (PoP), surface wind, cloud amount, ceiling height, visibility, and maximum/minimum (max/min) temperature. Verification summaries are provided for both forecast cycles, 0000 and 1200 GMT. The scores are those recommended in the NWS National Verification Plan (National Weather Service, 1982).

The local public weather PoP and max/min forecasts used for verification were official forecasts obtained from the Coded City Forecast (FPUS4) bulletin. All of the local aviation weather forecasts (except for cloud amount) were obtained from NWS official terminal forecasts (FT's). The local cloud amount forecasts were manually entered by the forecasters at the WSFO's. The local subjective forecasts may or may not be based on the objective guidance. Also, surface observations as late as 2 hours before the first valid forecast time may have been used in preparation of the local forecasts.

The automated guidance was based on forecast equations developed through application of the Model Output Statistics (MOS) technique (Glahn and Lowry, 1972). In particular, these prediction equations were derived by using archived surface observations and forecast fields from the Limited-area Fine Mesh (LFM) model (Gerrity, 1977; Newell and Deaven, 1981; National Weather Service, 1981b). The surface observations used in these equations were taken at least 9 hours before the first verification valid time.

As noted in the sections which follow for each of the various weather elements, implementation of the new AFOS-era verification system has introduced significant changes from past verifications in regard to the characteristics of the local forecasts and verifying observations. For example, the local and guidance max/min temperature forecasts are now being verified by using max/min temperatures observed during 12-h instead of 24-h (calendar day) periods. Also, the cloud amount observations are given in terms of total sky cover rather than opaque sky cover. Many other changes are associated with

obtaining the local forecasts from the FT's. Hence, at this time, we do not think it is meaningful to compare results for the 1984 warm season with those for prior years which were based on the pre-AFOS verification system (e.g., Maglaras et al., 1984).

2. PROBABILITY OF PRECIPITATION

MOS PoP forecasts were produced by the warm season prediction equations described in Technical Procedures Bulletin No. 299 (National Weather Service, 1981a). This guidance was available for the first, second, and third periods, which correspond to 12-24, 24-36, and 36-48 hours, respectively, after 0000 and 1200 GMT. The predictors for the equation development were forecast fields from the LFM model and weather elements observed at the forecast site at 0300 or 1500 GMT. However, because of time constraints in day-to-day operations, surface observations at 0200 or 1400 GMT were used as input to the prediction equations about 50% of the time.

The forecasts were verified by computing Brier scores (Brier, 1950) for 93 of the 94 stations listed in Table 2.1. Please note that we used the standard NWS Brier score for PoP which is one-half the original score defined by Brier. Brier scores will vary from one station to the next and from one year to the next because of changes in the relative frequency of precipitation. In particular, the scores usually are better for periods of below normal precipitation. Therefore, we also computed the percent improvement over climate, that is, the percent improvement of Brier scores obtained from the local or guidance forecasts over analogous Brier scores produced by climatic forecasts. Climatic forecasts are defined as relative frequencies of precipitation by month and by station determined from a 15-yr sample (Jorgensen, 1967). Because local forecasters should be encouraged to depart from the guidance if they have reason to believe it is incorrect, the number of times local forecasters deviated from the guidance and the percent of these changes which were in the correct direction also were tabulated.

Tables 2.2 and 2.7 present the 1984 warm season results for all 93 stations combined for the 0000 and 1200 GMT cycle forecasts, respectively. Tables 2.3-2.6 and Tables 2.8-2.11 show scores for the NWS Eastern, Southern, Central, and Western Regions, for the 0000 and 1200 GMT cycles, respectively. Comparison of the Brier scores and improvements over climate in Table 2.2 indicates the 0000 GMT cycle local forecasts were better than the guidance for the first and second periods but worse for the third period. Local forecasters deviated from the guidance about 55% of the time and were correct when they did so 54%, 52%, and 49% of the time for the first, second, and third periods, respectively. On the regional level for the 0000 GMT cycle (Tables 2.3-2.6), the local forecasts for all regions and periods were as good as or better than the guidance except for the second-period forecasts for the Southern Region and the third-period forecasts for the Eastern, Southern, and Central Regions. Table 2.7 shows that, overall, the local forecasts were better than the guidance for the first period from 1200 GMT (2.8% improvement), but that the two sets of forecasts were about equal in skill for the second and third periods. Local forecasters deviated from the guidance about 55% of the time and were correct when they did so 55%, 48%, and 54% of the time for the first, second, and third periods, respectively. Except for the second-period forecasts for the Eastern and Southern Regions and the third-period forecasts for

the Southern Region, the local forecasts for all regions and periods (Tables 2.8-2.11) were as good as or better than the guidance.

In terms of percent improvement over climate, the first- and third-period local and guidance forecasts for the 0000 GMT cycle were worse than those for the 1983 warm season (Maglaras et al., 1984), but the 1984 forecasts were better for the second period. For the 1200 GMT cycle, the 1984 forecasts were worse than those for the previous warm season for all three periods.

3. SURFACE WIND

The objective surface wind forecasts were generated by the warm season, LFM-based equations described in Technical Procedures Bulletin No. 335 (National Weather Service, 1983b). Prior to the 1984 warm season, the surface wind prediction equations were rederived in order to account for the most recent data available from the LFM model.

We verified the 12- and 18-h forecasts from both 0000 and 1200 GMT. The previous AFOS-era verification report (Carter et al., 1984) also contained statistics for 30-h guidance and local surface wind forecasts. However, in response to a recommendation from the National Verification Committee, the 30-h forecasts were replaced by 24-h forecasts during the middle of the 1984 warm season. Hence, for this report, we were not able to archive enough forecasts of either the 24- or 30-h projection to obtain a meaningful verification sample.

The objective surface wind forecast is defined in the same way as the observed wind, namely, the 1-min average wind direction and speed for a specific time. All objective forecasts of wind speed were adjusted by an "inflation" technique (Klein et al., 1959) involving the multiple correlation coefficient and the mean value of wind speed for each particular station and forecast valid time.

The local forecasts were obtained from the FT's. Since the FT's do not mention wind if the speed is expected to be less than 10 kt, the wind forecasts were verified in two ways. First, for those cases in which the speed forecasts from both the FT and MOS were ≥ 10 kt, the mean absolute error (MAE) and the mean algebraic error of the speed forecasts were computed. Cases where the observed wind was calm were then eliminated from this sample and the MAE of direction was computed. Second, for all cases where both the FT's and the MOS forecasts were available, skill score, percent correct, bias by category, 2

¹The skill score used throughout this report is the Heidke skill score (Panofsky and Brier, 1965).

²In the discussion of surface wind, cloud amount, ceiling height, and visibility, bias by category refers to the number of forecasts of a particular category (event) divided by the number of observations of that category. A value of 1.0 denotes unbiased forecasts for a particular category.

and the threat score³ were computed from contingency tables of wind speed. The definitions of the categories used in the contingency tables for wind speed and direction are given in Table 3.1. The threat score used here was calculated by combining events of the upper two categories. In addition, for all cases in which the wind speeds (forecasts or corresponding observations) were at least 10 kt, the skill score for the wind direction forecasts was computed from contingency tables. The 94 stations used in the verification are listed in Table 2.1.

It is important to note that several fundamental differences exist between the objective MOS forecasts and the local forecasts obtained from the FT's. In particular, the FT's are not as precise in regard to valid time as are the objective forecasts. Another point that needs to be considered is the nature of the wind forecast in the FT. It is unclear whether aviation forecasters tend to concentrate on a specific extreme wind or on an average wind over the forecast period. In this respect, an additional comparison was made between the objective and local forecasts by using the highest observed wind within ± 3 hours surrounding the verification time. Since the results were similar to those based on the single observation at the verification time, they are not presented here. Due to these and other possible differences between the MOS forecasts and local forecasts as obtained from the FT's, only conclusions of a general nature should be drawn from the verification statistics.

In addition, 42-h forecasts of winds \geq 22 knots were collected as part of the AFOS-era verification system. The local forecasts were manually entered by forecasters at the WSFO's. However, the first warm season of this verification program did not result in a sufficient sample of 42-h forecasts for a meaningful comparative verification. We hope this situation will improve as the local forecasters become more familiar with the new system.

The results for all 93 (94) stations combined for the 0000 (1200) GMT cycles are presented in Tables 3.2-3.4 (Tables 3.9-3.11). The direction MAE's and skill scores for the 0000 and 1200 GMT cycles, as given in Tables 3.2 and 3.9, show that the local forecasters were superior to the guidance at the 12-h projection. In contrast, for the 18-h projection, the guidance was better than the locals and by a wider margin. The speed MAE's indicate that the locals were superior except for the 18-h projection after 1200 GMT where the MAE's for both the guidance and the locals were the same. The skill scores for speed show that the guidance had better skill scores except for the 12-h projection after 0000 GMT. For percent correct, the locals were slightly better than the guidance with the exception of the 18-h projection from 1200 GMT where the guidance had a slight advantage. In terms of the mean algebraic errors, the local forecasters were superior for all projections. The speed bias by category in Tables 3.2 and 3.9 and the contingency tables in Tables 3.4 and 3.11 show that for the 0000 GMT cycle, the guidance generally overestimated winds stronger than 17 kt (i.e., categories 3, 4, 5, and 6) for both projections. In contrast, the locals underestimated speeds in these same categories. The speed bias by category for the 1200 GMT cycle indicates the

 $^{^{3}}$ Threat score = H/(F+O-H), where H is the number of correct forecasts of a category, and F and O are the number of forecasts and observations of that category, respectively.

the local forecasters underestimated wind speeds greater than 17 kt (i.e., categories 3, 4, 5, and 6). In terms of the threat score for categories 5 and 6 combined, the locals were superior to the guidance, except for the 18-h projection after 1200 GMT.

Tables 3.5-3.8 and 3.12-3.15 show scores for the NWS Eastern, Southern, Central, and Western Regions for 0000 and 1200 GMT, respectively. The regional comparisons have the same general characteristics as were noted for the entire group of stations. Of course, for some scores, the comparisons differ from region to region.

4. CLOUD AMOUNT

During the 1984 warm season, the objective cloud amount forecasts were produced by the prediction equations described in Technical Procedures Bulletin No. 303 (National Weather Service, 1981c). These regional, generalized-operator equations used LFM model output and 0300 (1500) GMT surface observations to produce probability forecasts of the four categories of cloud amount shown in Table 4.1. We converted the probability estimates to "best category" forecasts in a manner which produced good bias characteristics, that is, a bias value of approximately 1.0 for each category. The threshold technique described in Technical Procedures Bulletin No. 303 was used to obtain the best category.

We compared the local forecasts with a matched sample of guidance forecasts for 92 of the 94 stations listed in Table 2.1 for the 12-, 18-, and 24-h projections from 0000 and 1200 GMT. The local forecasts and surface observations used for verification were converted to the cloud amount categories given in Table 4.1. Four-category (clear, scattered, broken, and overcast), forecast-observed contingency tables were prepared from the local and objective categorical predictions. Using these tables, we computed the percent correct, skill score, and bias by category. In past verifications (except for the 1983-84 cool season), only opaque sky cover amounts from surface observations were used in determining the observed categories. However, the hourly surface reports from which the verifying observations are being taken do not include total opaque sky cover as part of the observation; hence, thin clouds are also taken into account. For example, a report of overcast with eight tenths opaque and two tenths thin which was put in the broken category previously, now is categorized as overcast. The result of this change is to decrease (increase) the number of observations of the broken (overcast) category compared to previous verifications. This change has greatly affected the overall bias by category statistics for the guidance and local forecasts.

The results for all stations combined are shown in Tables 4.2 and 4.7 for the 0000 and 1200 GMT cycle forecasts, respectively. In terms of skill score and percent correct, the 0000 GMT cycle local forecasts did better than the guidance for the 12-h projection; there was little difference at 18 hours, while MOS was better at 24 hours. Examination of the biases by category shows that the guidance forecasts were better (i.e., closer to 1.0) than the locals for seven out of the 12 possible projections and categories. The bias results for local and guidance forecasts were, in general, extremely poor. For the clear and scattered categories, the biases by category are about the same as for previous warm seasons. However, scores for the broken and overcast

categories are much worse than in previous warm seasons for both the local and guidance forecasts; most likely, this was because of the changes in the verification process mentioned earlier. For 1200 GMT (Table 4.7), the local forecasts were better than the guidance in terms of skill score and percent correct for only the 12-h projection. Again, the biases by category show that the guidance was slightly better than the locals.

Tables 4.3-4.6 and Tables 4.8-4.11 show scores for the NWS Eastern, Southern, Central, and Western Regions, for the 0000 and 1200 GMT cycles, respectively. For both cycles, the comparisons varied from region to region and from score to score.

5. CEILING AND VISIBILITY

During the 1984 warm season, the ceiling and visibility guidance was produced by the prediction equations described in Technical Procedures Bulletin No. 303 (National Weather Service, 1981c). Operationally, the guidance was based primarily on LFM model output and 0300 (1500) GMT surface observations.

Verification scores were computed for both local and guidance forecasts for the stations listed in Table 2.1. The local forecasts were obtained from the FT's. Persistence based on an observation taken at 0900 (2100) GMT for the 0000 (1200) GMT forecast cycle was used as a standard of comparison. The objective forecasts were verified for both cycles for 12-, 18-, and 24-h projections. The local and persistence forecasts were verified for 12-, 15-, 18-, and 24-h projections from 0000 and 1200 GMT. On station, the guidance and persistence observations usually were available in time for preparation of the local forecasts. As was the case for surface wind, the local ceiling and visibility forecasts from the FT's are not given for a specific valid time. Hence, any comparisons with the results for the objective forecasts must be of a general nature.

We constructed forecast-observed contingency tables for the four categories of ceiling and visibility given in Table 5.1. These categories were used for computing several different scores: bias by category, percent correct, skill score, and log score. We have summarized the results in Tables 5.2-5.5. It should be noted that the persistence and local forecasts for the 12-, 15-, 18-, and 24-h projections are actually 3-, 6-, 9-, and 15-h forecasts, respectively, from the latest available surface observation, and in this sense, the guidance forecasts for the 12-, 18-, and 24-h projections are actually 9-, 15-, and 21-h forecasts.

Tables 5.2 and 5.4 show the scores for the ceiling forecasts from 0000 and 1200 GMT, respectively. In terms of log score, skill score, and percent correct, the 0000 GMT cycle local forecasts were as good as or better than persistence for all four projections, and as good as or better than the guidance for the 12- and 18-h projections (guidance forecasts are not

 $^{^4\}mathrm{This}$ score is proportional to the absolute value of $\log_{10}f_{1}$ - $\log_{10}O_{1}$ where f_{1} is the forecast category for each case and O_{1} is the observed category for each case. The result is averaged over all cases and scaled by multiplying by 50.

available for the 15-h projection). The guidance was better than the locals at 24 hours. Also, the guidance was better than persistence for the 18- and 24-h projections. The 1200 GMT cycle comparisons among the three forecast systems were similar to those for the 0000 GMT cycle, except the log and skill scores for local forecasts were also better than the guidance for the 24-h projection, and persistence was better than the locals at 12 hours. In terms of bias by category, the guidance had the best overall scores for both cycles.

Tables 5.3 and 5.5 show the scores for the visibility forecasts for the 0000 and 1200 GMT cycles, respectively. In terms of log score and percent correct, the 0000 GMT cycle local forecasts of visibility were better than the guidance for all projections; the local forecasts also were better than persistence for the 15-, 18-, and 24-h projections but not for the 12-h projection. The guidance was better than persistence for the 18- and 24-h projections. terms of skill score, the guidance was as good as or better than the local forecasts for the 18- and 24-h projections. The 1200 GMT cycle persistence forecasts of visibility were better than the locals for all four projections in terms of log score and percent correct except for the log score at 24 hours. The locals were better than the guidance for all three projections except for percent correct at 18 hours. In terms of skill score, the locals were better than persistence for the 18- and 24-h projections, and they were better than the guidance for all three projections. Overall, the guidance had slightly better biases by category than the locals for both the 0000 and 1200 GMT cycles.

6. MAXIMUM/MINIMUM TEMPERATURE

The max/min temperature guidance for the 1984 warm season was generated by the LFM-based regression equations described in Technical Procedures Bulletin No. 344 (National Weather Service, 1984). The guidance was based on equations developed by stratifying archived LFM model forecasts, station observations, and the first two harmonics of the day of the year into seasons of 3-mo duration (Dallavalle et al., 1980). We defined spring as March-May, summer as June-August, and fall as September-November. Since the MOS max/min guidance is valid for the local calendar day, the first period (approximately 24-h) objective forecast of the max based on 0000 GMT model data is for the calendar day starting at the subsequent midnight. The max/min guidance for the other periods (projections of approximately 36, 48, and 60 hours) also correspond to specific calendar days. In contrast, the subjective local forecasts are for daytime max and nighttime min. Thus, the first period subjective max forecast from 0000 GMT data is for today's high. The second period forecast is for tonight's low and so forth. A similar procedure is followed for the 1200 GMT cycle, except the first period is tonight's min. For the local forecast, daytime is defined to be approximately from 1200 to 0000 GMT. Nighttime then extends approximately from 0000 to 1200 GMT except in the western parts of the Central and Southern Regions and throughout the entire Western Region where nighttime may go to nearly 1800 GMT.

In this report, we present results for both objective guidance and subjective local forecasts which were verified by using a 12-h synoptic observation obtained from the AFOS-era verification system. In particular, the 0000 GMT synoptic report of the max is valid for the 1200 to 0000 GMT period, while the 1200 GMT observation for the preceding 0000 to 1200 GMT period is used for the min. Note that the 0000 GMT max temperature observation represents the daytime

high most of the time during the warm season, particularly in the eastern half of the United States. However, in the western part of the country, the daytime max occasionally occurs after 0000 GMT (1600 LST). Obviously, for these cases the 0000 GMT observation is inadequate. In an analogous manner, the 1200 GMT min temperature observation occasionally underestimates the actual nighttime low. In the western United States, where 1200 GMT corresponds to 0400 LST, the nighttime low often occurs after 1200 GMT. Thus, we suspect that the errors for both the max and min forecasts are overestimates. Unfortunately, no existing synoptic report accurately represents the daytime max or nighttime min in all circumstances. However, the local forecasters have the option of replacing the observed max or min from the synoptic report with a more representative observation. This problem with the verifying observations will be corrected for the 1984-85 cool season when new local software is implemented to derive an appropriate daytime high and nighttime low from a combination of synoptic and hourly reports.

We verified the local and MOS max/min temperature forecasts for both the 0000 and 1200 GMT cycles. The mean algebraic error (forecast minus observed temperature), mean absolute error, the number of absolute errors >10°F, the probability of detection⁵ of min temperatures <32°F, and the false alarm ratio⁶ for min temperatures <32°F were computed for 93 stations in the conterminous United States (Table 2.1). At 0000 (1200) GMT, the local max temperature forecasts are valid for daytime periods ending approximately 24 (36) and 48 (60) hours after 0000 (1200) GMT. Similarly, at 0000 (1200) GMT, the local min temperature forecasts are valid for nighttime periods ending approximately 36 (24) and 60 (48) hours after 0000 (1200) GMT.

For all stations combined, the results for 0000 and 1200 GMT are shown in Tables 6.1 and 6.6, respectively. A matched sample of approximately 14,500 cases per forecast projection was available. Similarly, Tables 6.2-6.5 give the 0000 GMT verification scores for the Eastern, Southern, Central, and Western Regions, respectively. Tables 6.7-6.10 show analogous scores by NWS region for the 1200 GMT cycle.

For all regions, both forecast cycles, and all projections, the local and the MOS max temperature forecasts exhibited a warm bias (positive algebraic error). Tables 6.1 and 6.6 show for all stations combined that the bias in the MOS max forecasts ranged from 0.7°F for tomorrow's max (0000 GMT) to 1.2°F for the day after tomorrow's max (1200 GMT). For the local forecasts, the biases for the same projections were 0.6°F and 1.0°F, respectively. These warm biases in the max forecasts were persistent from region to region. However, the bias in the MOS guidance was always larger than that of the local forecasts except for two projections in the Southern Region. As discussed earlier, at least a portion of the forecast bias (both local and MOS) may be related to the time of observation and not to a specific meteorological factor. In terms of mean absolute

⁵Here, the probability of detection is defined to be the fraction of time the min temperature was correctly forecast to be $\leq 32^{\circ}F$ when the previous day's min was $\geq 40^{\circ}F$.

⁶Here, the false alarm ratio is defined to be the fraction of forecasts of <32°F that failed to verify when the previous day's min was ≥40 °F.

error, the local max forecasts averaged 0.2°F more accurate than the MOS guidance for the four projections and all stations combined. This superiority was evident in the local forecasts for each of the four regions although the greatest difference in accuracy between the MOS and the subjective forecasts occurred in the Western Region. Note that for all stations combined, the percentage of absolute errors greater than 10°F exceeded 5% only for the forecast of the day after tomorrow's max from 1200 GMT data (Table 6.6).

Analogous trends are evident in the verification statistics for the min forecasts. For all stations combined, both the MOS and local forecasts showed a cold bias (negative algebraic error) in each of the four projections. With the exception of the forecast for tonight's min (0000 GMT) in the Southern Region, the regional results had the same cold tendency. The largest bias occurred in the Western Region, but this feature may be due to the observation time and not to any meteorological cause. In nearly all regions and all projections, the bias in the local forecasts was less than that for the MOS guidance. In terms of mean absolute error, the local min temperature forecasts for all regions and all projections averaged 0.2°F more accurate than the guidance. In fact, this improvement of the local forecasts remained relatively constant from region to region. Generally, MOS predicted more "critical events" than did the locals, so the probability of detection of temperatures <32°F was greater for the guidance, but the local forecasts had a smaller false alarm ratio. However, the small number of cases during the warm season make these values rather unstable.

The verifications in Tables 6.1 and 6.6 indicate that for approximately similar projections, the max temperature was slightly more difficult to predict than the min. As an example, the mean absolute error for the 36-h projection of the max (tomorrow's max) from 1200 GMT was 3.4 and 3.7°F for the local forecasts and the guidance, respectively. For the 36-h projection of the min (tonight's min) from 0000 GMT, the corresponding errors were 3.1 and 3.3°F for the local forecasts and the guidance, respectively. For all four projections combined, the absolute error for both the local and MOS max forecasts averaged 0.2°F more than for the min forecasts. This trend in the relative difficulty of forecasting the max or min was generally evident in the scores for all regions and all projections, but it was most pronounced in the Eastern Region. Usually, the max is more difficult to forecast than the min during the warm season because of the greater variability of the max temperature. The difference in predictability is likely due to the effects of localized convective activity on daytime heating (e.g., Schwartz, 1984). Clearly, both the guidance and the local forecasters often have difficulties in recognizing and predicting the impact of mesoscale convective outbreaks.

SUMMARY

Highlights of the 1984 warm season verification results, summarized by general type of weather element, are:

o Probability of Precipitation - The PoP verification involved 93 stations and forecast projections of 12-24, 24-36, and 36-48 hours from 0000 and 1200 GMT. The NWS Brier scores for all stations combined indicate the local forecasts were better than the guidance for the first period (on the order of 3.0%), but there was little

difference in accuracy for the two sets of forecasts for the second and third periods. Depending on the projection and cycle, the local forecasters deviated from the guidance about 55% of the time, and these changes were in the correct direction from 48% to 55% of the time.

- Surface Wind The AFOS-era wind verification involved the comparison of surface wind speed and direction forecasts for 93 (94) stations for projections of 12 and 18 hours from 0000 (1200) GMT. In this system, the local forecasts were obtained from NWS official terminal forecasts. Several fundamental differences exist between the MOS wind forecasts and those in the FT's. For example, the FT's are not as precise in regard to valid time as are the objective forecasts. Due to these differences, only conclusions of a general nature can be drawn from the results. The statistics for all stations combined for wind direction indicate the locals were able to improve upon MOS for the 12-h forecast projection from both 0000 and 1200 GMT. The guidance for the 18-h projection for both cycles, on the other hand, was superior to the locals and by a wider margin. The overall results for the speed forecasts indicate that the locals were generally better than the guidance in terms of the mean absolute and mean algebraic errors. Also, the locals were marginally better than the guidance for percent correct for all but the 18-h projection after 1200 GMT. In terms of skill score, MOS was superior for all but the 12-h projection after 0000 GMT.
- Cloud Amount The verification for cloud amount involved 92 stations and forecasts for projections of 12, 18, and 24 hours from 0000 and 1200 GMT. The skill scores and percents correct for all stations combined indicate the 0000 GMT cycle local forecasts were better than the guidance for the 12-h projection; there was little difference at 18 hours, and MOS was better at 24 hours. For the 1200 GMT cycle, the local forecasts were better at the 12-h projection and guidance was better at the 18- and 24-h projections. In terms of bias by category (clear, scattered, broken, and overcast) for both cycles and all projections, the results varied by category and forecast projection, but overall, the guidance was slightly better.
- Ceiling and Visibility The verification involved the comparison of 0 local forecasts, MOS guidance, and persistence for 93 (94) stations for projections of 12, 15, 18, and 24 hours from 0000 (1200) GMT. Direct comparison of local, MOS, and persistence forecasts was possible for the 12-, 18-, and 24-h projections. These are actually 3-, 9-, and 15-h forecasts from the latest available surface observations for the locals and persistence, and in this sense, they are 9-, 15-, and 21-h forecasts for the guidance. For both forecast cycles, the log score, percent correct, and skill score indicate that the locals were better than the guidance at the 12-h projection, but not as good as persistence. For the 15-h projection, the locals were better than (about the same as) persistence for ceiling (visibility). For the 18-h projection, most scores indicate that the local forecasts of ceiling and visibility were better than the guidance and persistence forecasts for both cycles; the guidance forecasts also were better than persistence, except for the 1200 GMT cycle visibility forecasts. For the 24-h

- projection, indications of accuracy and skill varied considerably by cycle, element, and score.
- Maximum/Minimum Temperature Objective and local forecasts were verified for 93 stations for both the 0000 and 1200 GMT cycles. At 0000 (1200) GMT, the local maximum temperature forecasts were valid for daytime periods approximately 24 (36) and 48 (60) hours in advance, while the minimum temperature forecasts were valid for nighttime periods ending approximately 36 (24) and 60 (48) hours after initial model time. In contrast, the MOS guidance was valid for calendar day periods. The verifying observations were usually max or min temperatures for 12-h periods ending at 0000 and 1200 GMT, respectively. For all stations and projections combined, we found that the mean absolute errors of the local max and min temperature forecasts averaged 0.2°F less than that for the MOS guidance. Clearly, the local forecasters are improving over the guidance, although some of this improvement probably is associated with the differences between the valid periods of the two types of forecasts and the verifying observations. As is usual during the warm season, the minimum temperature forecasts verified better for the same projection than did the maximum temperature forecasts.

8. ACKNOWLEDGMENTS

We are grateful to Fred Marshall and Eston Pennington for assistance in archiving the data, and also to Belinda Howard and Gladys Hodge for typing the text and the many tables shown in this report.

REFERENCES

- Brier, G. W., 1950: Verification of forecasts expressed in terms of probability. Mon. Wea. Rev., 78, 1-3.
- Carter, G. M., V. J. Dagostaro, J. P. Dallavalle, G. W. Hollenbaugh, and G. J. Maglaras, 1984: AFOS-era verification of guidance and local aviation/public weather forecasts--No. 1 (October 1983-March 1984). TDL Office
 Note 84-15, National Weather Service, NOAA, U.S. Department of Commerce, 58 pp.
- Dallavalle, J. P., J. S. Jensenius, Jr., and W. H. Klein, 1980: Improved surface temperature guidance from the limited-area fine mesh model. Preprints

 Eighth Conference on Weather Forecasting and Analysis, Denver, Amer. Meteor. Soc., 1-8.
- Gerrity, J. P., Jr., 1977: The LFM model--1976: A documentation. NOAA

 Technical Memorandum NWS NMC-60, National Oceanic and Atmospheric Administration, U.S. Department of Commerce, 68 pp.
- Glahn, H. R., and D. A. Lowry, 1972: The use of Model Output Statistics (MOS) in objective weather forecasting. J. Appl. Meteor., 11, 1203-1211.
- Jorgensen, D. L., 1967: Climatological probabilities of precipitation for the conterminous United States. ESSA Tech. Report WB-5, Environmental Science Services Administration, U.S. Department of Commerce, 60 pp.

AWS TECHNICAL LIBRARY FL 4414 859 BUCHANAN STREET SCOTT AFB IL 62225-5118

- Klein, W. H., B. M. Lewis, and I. Enger, 1959: Objective prediction of fiveday mean temperatures during winter. J. Meteor., 16, 672-682.
- Maglaras, G. J., G. M. Carter, J. P. Dallavalle, G. W. Hollenbaugh, and B. E. Schwartz, 1984: Comparative verification of guidance and local aviation/public weather forecasts-No. 16 (April 1983-September 1983). TDL Office Note 84-4, National Weather Service, NOAA, U.S. Department of Commerce, 69 pp.
- Miller, R. L., M. M. Heffernan, and D. P. Ruth, 1984: AFOS-era forecast verification. NOAA Techniques Development Laboratory Computer Program NWS TDL CP 84-3, National Weather Service, NOAA, U.S. Department of Commerce, 44 pp.
- National Weather Service, 1981a: The use of Model Output Statistics for predicting probability of precipitation (PoP). NWS Technical Procedures

 Bulletin No. 299, National Oceanic and Atmospheric Administration, U.S.

 Department of Commerce, 12 pp.
- , 1981b: More efficient LFM by applying fourth order operators. NWS

 Technical Procedures Bulletin No. 300, National Oceanic and Atmospheric Administration, U.S. Department of Commerce, 9 pp.
- , 1981c: The use of Model Output Statistics for predicting ceiling, visibility, cloud amount, and obstructions to vision. NWS Technical Procedures

 Bulletin No. 303, National Oceanic and Atmospheric Administration, U.S.

 Department of Commerce, 11 pp.
- , 1982: <u>National Verification Plan</u>. National Oceanic and Atmospheric Administration, U.S. Department of Commerce, 81 pp.
- , 1983a: Public/aviation forecast verification. NWS Operations Manual, Chapter C-73, National Oceanic and Atmospheric Administration, U.S. Department of Commerce, 18 pp.
- , 1983b: The use of Model Output Statistics for predicting surface wind.

 NWS Technical Procedures Bulletin No. 335, National Oceanic and Atmospheric Administration, U.S. Department of Commerce, 12 pp.
- , 1984: Automated maximum/minimum temperature, 3-hourly surface temperature, and 3-hourly surface dew point guidance. NWS Technical Procedures Bulletin No. 344, National Oceanic and Atmospheric Administration, U.S. Department of Commerce, 13 pp.
- Newell, J. E., and D. G. Deaven, 1981: The LFM-II model--1980. NOAA Technical Memorandum NWS NMC-66, National Oceanic and Atmospheric Administration, U.S. Department of Commerce, 20 pp.
- Panofsky, H. A., and G. W. Brier, 1965: Some Applications of Statistics to Meteorology. Pennsylvania State University, University Park, 224 pp.
- Schwartz, B. E., 1984: Typical warm season MOS guidance errors. <u>Preprints</u>

 Tenth Conference on Weather Forecasting and Analysis, Clearwater Beach,

 Amer. Meteor. Soc., 50-56.

Table 2.1. Ninety-four stations used for comparative verification of MOS guidance and local probability of precipitation, surface wind, cloud amount, ceiling height, visibility, and max/min temperature forecasts. Please note that LAX was not included in the PoP and max/min temperature verifications. LAX and SAN were not included in the cloud amount verifications. TCC was not available during the 0000 GMT cycle for surface wind, ceiling height, and visibility.

DCA	Washington, D.C.	ORF	Norfolk, Virginia
PWM	Portland, Maine	CON	Concord, New Hampshire
BOS	Boston, Massachusetts	PVD	Providence, Rhode Island
ALB	Albany, New York	BTV	Burlington, Vermont
BUF	Buffalo, New York	SYR	Syracuse, New York
LGA	New York (LaGuardia), New York	EWR	Newark, New Jersey
RDU	Raleigh-Durham, North Carolina	CLT	Charlotte, North Carolina
CLE	Cleveland, Ohio	CMH	Columbus, Ohio
PHL	Philadelphia, Pennsylvania	ACY	Atlantic City, New Jersey
PIT	Pittsburgh, Pennsylvania	ERI	Erie, Pennsylvania
CAE	Columbia, South Carolina	CHS	Charleston, South Carolina
CRW	Charleston, West Virginia	BKW	Beckley, West Virginia
BHM	Birmingham, Alabama	MOB	Mobile, Alabama
LIT	Little Rock, Arkansas	FSM	Fort Smith, Arkansas
MIA	Miami, Florida	TPA	Tampa, Florida
ATL	Atlanta, Georgia	SAV	Savannah, Georgia
MSY	New Orleans, Louisiana	SHV	Shreveport, Louisiana
JAN	Jackson, Mississippi	MEI	Meridian, Mississippi
ABQ	Albuquerque, New Mexico	TCC	Tucumcari, New Mexico
OKC	Oklahoma City, Oklahoma	TUL	Tulsa, Oklahoma
MEM	Memphis, Tennessee	BNA	Nashville, Tennessee
DFW	Dallas-Ft. Worth, Texas	ABI	Abilene, Texas
LBB	Lubbock, Texas	ELP	El Paso, Texas
SAT	San Antonio, Texas	IAH	Houston, Texas
DEN	Denver, Colorado	GJT	Grand Junction, Colorado
ORD	Chicago (O'Hare), Illinois	SPI	Springfield, Illinois
IND	Indianapolis, Indiana	SBN	South Bend, Indiana
DSM	Des Moines, Iowa	ALO	Waterloo, Iowa
TOP	Topeka, Kansas	ICT	Wichita, Kansas
SDF	Louisville, Kentucky	LEX	Lexington, Kentucky
DTW	Detroit, Michigan	GRR	Grand Rapids, Michigan
MSP	Minneapolis, Minnesota	DLH	Duluth, Minnesota
STL	St. Louis, Missouri	MCI	Kansas City, Missouri
OMA	Omaha, Nebraska	LBF	North Platte, Nebraska
BIS	Bismarck, North Dakota	FAR	Fargo, North Dakota
FSD	Sioux Falls, South Dakota	RAP	Rapid City, South Dakota
MKE	Milwaukee, Wisconsin	MSN	Madison, Wisconsin
CYS	Cheyenne, Wyoming	CPR	Casper, Wyoming
PHX	Phoenix, Arizona	TUS	Tucson, Arizona
LAX	Los Angeles, California	SAN	San Diego, California
SFO	San Francisco, California	FAT	Fresno, California
BOI	Boise, Idaho	PIH	Pocatello, Idaho
GTF	Great Falls, Montana	HLN	Helena, Montana
RNO	Reno, Nevada	LAS	
PDX	Portland, Oregon	MFR	
		CDC	
SLC	Salt Lake City, Utah	ODO	dedai dity, dta



Table 2.2. Comparative verification of MOS guidance and local PoP forecasts for 93 stations, 0000 GMT cycle.

		% Imp.	% Imp.	No.	No. of	% Changes
Type of Forecast	Brier Score	Over Guid.	Over Clim.	of Cases	Changes to Guid.	Correct Direction
MOS	.1048		29.0			
Local	.1013	3.4	31.4	14412	8325	54.2
MOS	.1101		23.9			
Local	.1095	0.6	24.3	14355	7956	52.3
MOS	.1213		19.0			
Local	.1222	-0.8	18.3	14378	7938	48.6
	MOS Local MOS Local	MOS .1048 Local .1013 MOS .1101 Local .1095 MOS .1213	MOS .1048 Local .1013 3.4 MOS .1101 Local .1095 0.6 MOS .1213	Type of Forecast Brier Score Over Guid. Over Clim. MOS Local .1048 .1013 3.4 31.4 MOS .1101 .1095 0.6 24.3 23.9 24.3 MOS .1213 19.0	Type of Brier Over Over of Clim. Cases MOS .1048 29.0 Local .1013 3.4 31.4 14412 MOS .1101 23.9 Local .1095 0.6 24.3 14355 MOS .1213 19.0	Type of Brier Over Over of Changes to Guid. MOS .1048

Table 2.3. Same as Table 2.2 except for 24 stations in the Eastern Region.

Projection (h)	Type of Forecast	Brier Score	<pre>% Imp. Over Guid.</pre>	% Imp. Over Clim.	No. of Cases	No. of Changes to Guid.	% Changes Correct Direction
12-24	MOS	.1177		35.5			
(1st period)	Local	.1177	0.0	35.5	3252	2039	52.9
24-36	MOS	.1250		29.5			
(2nd period)	Local	.1250	0.0	29.6	3236	1903	57.0
36-48	MOS	.1388		25.3			
(3rd period)	Local	.1403	-1.1	24.5	3235	1915	53.1

Table 2.4. Same as Table 2.2 except for 24 stations in the Southern Region.

Projection (h)	Type of Forecast	Brier Score	% Imp. Over Guid.	% Imp. Over Clim.	No. of Cases	No. of Changes to Guid.	% Changes Correct Direction
12-24	MOS	.1097		21.7			
(1st period)	Local	.1054	3.9	24.8	3891	2340	53.1
24-36	MOS	.0969		18.0			4 0.
(2nd period)	Local	.0985	-1.6	16.7	3822	2196	48.3
36-48	MOS	.1220		14.5	, £		
(3rd period)	Local	.1226	-0.5	14.1	3890	2281	49.4

Table 2.5. Same as Table 2.2 except for 28 stations in the Central Region.

Projection (h)	Type of Forecast	Brier Score	% Imp. Over Guid.	% Imp. Over Clim.	No. of Cases	No. of Changes to Guid.	% Changes Correct Direction
12-24	MOS	.1085		31.3			
(1st period)	Local	.1040	4.1	34.1	4554	2498	57.8
24-36	MOS	.1220		26.2			
(2nd period)	Local	.1205	1.2	27.1	4565	2394	57.6
36-48	MOS	.1284		19.0			
(3rd period)	Local	.1297	-1.1	18.2	4551	2326	46.9

Table 2.6. Same as Table 2.2 except for 17 stations in the Western Region.

Projection (h)	Type of Forecast	Brier Score	% Imp. Over Guid.	% Imp. Over Clim.	No. of Cases	No. of Changes to Guid.	% Changes Correct Direction
12-24	MOS	.0763		23.4			
(1st period)	Local	.0713	6.6	28.5	2715	1448	51.5
24-36	MOS	.0909		15.9	• .	` .	en e
(2nd period)	Local	.0881	3.1	18.5	2732	1463	43.3
36-48	MOS	.0872		13.7	·	· · · · · · · · · · · · · · · · · · ·	
(3rd period)	Loca1	.0872	0.0	13.7	2702	1416	44.1

Table 2.7. Comparative verification of MOS guidance and local PoP forecasts for 93 stations, 1200 GMT cycle.

Projection (h)	Type of Forecast	Brier Score	% Imp. Over Guid.	% Imp. Over Clim.	No. of Cases	No. of Changes to Guid.	% Changes Correct Direction
12-24	MOS	.1039		28.1			*** *
(lst period)	Local	.1010	2.8	30.1	14312	8264	54.5
24-36	MOS	.1155		22.5			
(2nd period)	Local	.1156	-0.1	22.5	14346	7964	47.5
36-48	MOS	.1199		17.3			
(3rd period)	Local	.1198	0.1	17.3	14273	7753	54.3

Table 2.8. Same as Table 2.7 except for 24 stations in the Eastern Region.

Projection (h)	Type of Forecast	Brier Score	% Imp. Over Guid.	% Imp. Over Clim.	No. of Cases	No. of Changes to Guid.	% Changes Correct Direction
12-24	MOS	.1180		32.8			
(1st period)	Local	.1154	2.1	34.2	3197	1983	55.9
24-36	MOS	.1324		28.1			
(2nd period)	Local	.1339	-1.2	27.2	3206	1894	51.3
36-48	MOS	.1392		22.3			
(3rd period)	Local	.1385	0.5	22.7	3179	1860	56.7

Table 2.9. Same as Table 2.7 except for 24 stations in the Southern Region.

Projection (h)	Type of Forecast	Brier Score	% Imp. Over Guid.	% Imp. Over Clim.	No. of Cases	No. of Changes to Guid.	% Changes Correct Direction
12-24	MOS	.0947		19.6			-
(1st period)	period) Local .0928 2.0 21.3 3794	2256	51.4 /				
24-36	MOS	.1145		18.1	• ;		٠
(2nd period)	Local	.1147	-0.2	17.9	3854	2296	48.0
36-48	MOS	.1033		12.0			
(3rd period)	Loca1	.1048	-1.5	10.7	3781	2263	52.3

Table 2.10. Same as Table 2.7 except for 28 stations in the Central Region.

Projection (h)	Type of Forecast	Brier Score	% Imp. Over Guid.	% Imp. Over Clim.	No. of Cases	No. of Changes to Guid.	% Changes Correct Direction
12-24	MOS	.1153		30.9	•		
(1st period)	Local	.1120	2.9	32.9	4593	2637	57.1
24-36	MOS	.1235		22.8			
(2nd period)	Local	.1234	0.1	22.9	4580	2409	45.1
36-48	MOS	.1342		18.8			
(3rd period)	Local	.1341	0.1	18.8	4592	2315	58.2

Table 2.11. Same as Table 2.7 except for 17 stations in the Western Region.

Projection (h)	Type of Forecast	Brier Score	Z Imp. Over Guid.	% Imp. Over Clim.	No. of Cases	No. of Changes to Guid.	% Changes Correct Direction
12-24	MOS	.0810		24.6			
(1st period)	Local	.0770	4.9	28.3	2728	1388	52.6
24-36	MOS	.0834		18.3	• .		•
(2nd period)	Local	.0819	1.8	19.7	2706	1365	45.6
36-48	MOS	.0963		11.7	. 4		•
(3rd period)	Local	.0947	1.7	13.2	2721	1315	47.5

Table 3.1. Definition of the categories used for MOS guidance, local forecasts, and surface observations of wind direction and speed.

Category	Direction (degrees)	Speed (kt)
1	340-20	< 12
2	30-60	13-17
3	70-110	18-22
4	120-150	23-27
5	160-200	28-32
6	210-240	≥ 33
7	250-290	
8	300-330	***

Cases 14570 14597 No. 0.50 0.56 1.00 0.22 (9) 5 (No. Obs) 0.60 0.50 1.28 0.32 (25) Bias by Category 4 (No. Obs) 1.43 0.78 (23) 1.45 0.51 1.02 0.71 (2440) (574) 1.16 0.96 (820) (129) 3 (No. Obs) 1.46 1.28 Comparative verification of NOS guidance and local surface wind forecasts for 93 stations, 0000 GHT cycle. Contingency Table 1.00 1.15 2 (No. Obs) 0.99 1.02 (11445) 1 (No. Obs) 0.990.98 Speed Threat Score (>27 Kts) .18 .13 .16 . 20 Percent Frst. Correct 90.9 77.5 91.9 77.8 Skill Score .345 .398 . 388 .356 No. of Cases 2248 5464 Mean Alg. Error (Kts) 2.4 1.7 1.6 6.0 Hean Abs. Error (Kts) 3.0 3.5 3.4 3.2 Cases No. 2236 5443 Direction Skill Score .450 .577 607 . 544 Mean Abs. Error (Deg) 20 26 21 29 Fest. Local Type of Local Table 3.2. HOS MOS Fcst. Proj. (h) 12 8

2 3 4 67 14 6 94 56 10 37 180 75 4 61 156 2 11 83 0 0 6 0 1 4	1 309 2 76 3 19 085 4 3 6 4 7 19 8 117		~	7 9 202 62 62 323		67 7 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3		•	364 102 102 103 103 104 105 5 5 5 5 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6	4 5 7 4 31 102 49 364 2 70 0 12 0 5 201 570 120 12	2 4 5 6 2 7 33 4 3 111 31 7 24 113 102 6 49 364 1 2 70 2 0 12 2 0 12 3 0 5 186 201 570
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1				~	49 160 276 2	9 49 2 5 1 1 38 4 202 54 62 160 323 276 2	2 9 49 1 2 5 3 1 1 4 1 1 67 8 2 178 38 4 32 202 54 8 62 160 295 323 276 2	3 1 2 9 49 3 1 2 5 102 4 1 1 364 67 8 2 70 178 38 4 12 32 202 54 5 8 62 160 570 295 323 276 2	2 7 2 9 49 4 3 11 2 5 31 7 3 11 2 5 113 102 4 11 11 49 364 67 8 2 2 70 178 38 4 0 12 32 202 54 0 12 32 202 54 201 570 295 323 276 2	5 2 7 2 9 49 33 4 3 1 2 5 111 31 7 3 1 1 2 5 111 31 102 4 11 1 24 113 102 4 11 1 6 49 364 67 8 2 1 2 70 178 38 4 2 0 12 32 202 54 2 0 12 32 202 54 3 0 5 8 62 160 186 201 570 295 323 276 2	34 6 2 7 2 9 49 67 33 4 3 1 2 9 49 27 111 31 7 3 1 1 1 2 111 31 102 4 1 1 1 2 6 49 364 67 8 2 2 0 1 2 70 178 38 4 2 0 12 32 202 54 2 3 0 5 8 62 160 135 186 201 570 295 323 276 2 135 186 201 570 295 323 276 2
56 11 11 0 1	4 m 4 m 9 m 8 m		3 2 2 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	~	2 5 4 4 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	2 5 1 1 1 1 8 2 202 54 202 54 62 160 323 276 2	1 2 5 3 1 1 4 1 1 67 8 2 178 38 4 32 202 54 8 62 160 295 323 276 2	3 1 2 5 102 4 1 1 364 67 8 2 70 178 38 4 12 32 202 54 5 8 62 160 570 295 323 276 2	4 3 1 2 5 31 7 3 1 1 113 102 4 1 1 49 364 67 8 2 2 70 176 36 4 0 12 32 202 54 0 5 8 62 160 201 570 295 323 276 2	33 4 3 1 2 5 111 31 7 3 1 1 24 113 102 4 1 1 1 6 49 364 67 8 2 1 2 70 178 38 4 2 0 12 32 202 54 2 0 5 8 62 160 186 201 570 295 323 276 2	67 33 4 3 1 2 5 27 111 31 7 3 1 1 1 1 24 113 102 4 1 1 1 2 6 49 364 67 8 2 0 1 2 70 178 38 4 2 2 0 12 32 202 54 2 3 0 5 8 62 160 135 186 201 570 295 323 276 2
11 0 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	m 4 m 0 m 6 m		36 39	~	1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	3 1 1 4 1 1 67 8 2 178 38 4 32 202 54 8 62 160 295 323 276 2	7 3 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	31 7 3 1 1 113 102 4 1 1 49 364 67 8 2 2 70 176 38 4 0 12 32 202 54 0 5 8 62 160 201 570 295 323 276 2	111 31 7 3 1 1 24 113 102 4 1 1 6 49 364 67 8 2 1 2 70 178 38 4 2 0 12 32 202 54 3 0 5 8 62 160 186 201 570 295 323 276 2 186 201 570 295 323 276 2	27 111 31 7 3 1 1 1 24 113 102 4 1 1 2 6 49 364 67 8 2 0 1 2 70 178 38 4 2 2 0 12 32 202 54 2 3 0 5 8 62 160 135 186 201 570 295 323 276 2 Local
	4 00 00 00 10		7 8 8 8 8	~	1 2 2 54 160 276 2	1 1 8 2 38 4 202 54 62 160 323 276 2	67 8 2 178 38 4 32 202 54 8 62 160 295 323 276 2	102 4 1 1 364 67 8 2 70 178 38 4 12 32 202 84 5 8 62 160 570 295 323 276 2	113 102 4 1 1 49 364 67 8 2 2 70 178 38 4 0 12 32 202 54 0 5 8 62 160 201 570 295 323 276 2	24 313 102 4 1 1 6 49 364 67 8 2 1 2 70 178 38 4 2 0 12 32 202 54 3 0 5 8 62 160 186 201 570 295 323 276 2 Hoom	1 24 113 102 4 1 1 2 6 49 364 67 8 2 0 1 2 70 178 38 4 2 2 70 178 32 202 54 2 3 0 5 8 62 160 135 186 201 570 295 323 276 2 Local
11 0 1			36 28 36	~	2 4 54 160 276 2	8 2 38 4 202 54 62 160 323 276 2	67 8 2 178 38 4 32 202 54 8 62 160 295 323 276 2	364 67 8 2 70 178 38 4 12 32 202 84 5 8 62 160 570 295 323 276 2	49 364 67 8 2 2 70 178 38 4 0 12 32 202 54 0 5 8 62 160 201 570 295 323 276 2	6 49 364 67 8 2 1 2 70 178 38 4 2 0 12 32 202 54 3 0 5 8 62 160 186 201 570 295 323 276 2	2 6 49 364 67 8 2 0 1 2 70 178 38 4 2 2 0 12 32 202 54 2 3 0 5 8 62 160 135 186 201 570 295 323 276 2 Local
0 - 5			* 6 E 9	4 294 54 309 160 283 276 2236	54 54 160 276 2	38 4 202 54 62 160 323 276 2	178 38 4 32 202 54 8 62 160 295 323 276 2	70 178 38 4 12 32 202 54 5 8 62 160 570 295 323 276 2	2 70 178 38 4 0 12 32 202 54 0 5 8 62 160 201 570 295 323 276 2	1 2 70 178 38 4 2 0 12 32 202 54 3 0 5 8 62 160 186 201 570 295 323 276 2	0 1 2 70 178 38 4 2 2 0 12 32 202 54 2 3 0 5 8 62 160 135 186 201 570 295 323 276 2
- 5			36	~	54 160 276 2	202 54 62 160 323 276 2	32 202 54 8 62 160 295 323 276 2	12 32 202 54 5 8 62 160 570 295 323 276 2	0 12 32 202 54 0 5 8 62 160 201 570 295 323 276 2	2 0 12 32 202 54 3 0 5 8 62 160 186 201 570 295 323 276 2	2 2 0 12 32 202 54 2 3 0 5 8 62 160 135 186 201 570 295 323 276 2
~			36 33		276 2	52 160	8 62 160	5 8 62 160 570 295 323 276 2	0 5 8 62 160 201 570 295 323 276 2	3 0 5 8 62 160 186 201 570 295 323 276 2 iocal	2 3 0 5 8 62 160 135 186 201 570 295 323 276 2 10cal
			8		276	323 276	295 323 276	570 295 323 276	201 570 295 323 276	186 201 570 295 323 276 Local	135 186 201 570 295 323 276 Hocel
210 328 343							,	•		leod!	i eco i
							Local	1.00°1	Local		
2 3 4			H	89			7 8	7 8	7 8	4 5 6 7 8	3 4 5 6 7 8
75 7 10	1 279		11	40 277						1 4 5 6 40	6 1 4 5 6 40
108 53 11	2 61		77	3 144	1 3 144	0 1 3 144				3 2 0 1 3	38 3 2 0 1 3
37 163 85	3 22		82	0 182	0 0 182	•	0,	0,	8 2 0 0	36 8 2 0 0	119 36 8 2 0 0
6 52 200	7 7 590		13	1 247	3 1 247	2 3 1 247		2 3	80 2 3 1	144 80 2 3 1	14 144 80 2 3 1
1 16 158	. 5 11		90	2 500	7 4 500	7 2 500	7	7 2 77	392 44 7 4	44 392 44 7 4	44 392 44 7 4
0 4 19	. 6 7		76	4 294		4	7 07	176 40 4	176 40 4	176 40 4	1 1 69 176 40 4
5 0 7	7 18		50	11 309		11	111 111	39 177 71	39 177 71	4 10 39 177 71	0 4 10 39 177 71
3 9 1	8 130	,	8 3	175 283		175	74 115	74 115	4 6 44 175	0 4 6 44 175	3 0 4 6 44 175
239 301 495	T 532		36	298 2236		298	278 298	274 278 298	569 274 278 298	233 569 274 278 298	186 233 569 274 278 298

Table 3.4. Contingency tables for MOS guidance and local surface wind speed forecasts for 93 stations, 0000 GMT cycle. 11445 2440 2440 14597 104 574 18-h Forecasts Local HOS 737 407 1003 11640 2487 10208 1163 995 10100 1186 11228 2444 1041 1284 OBS OBS 14570 14570 12-h Forecasts Local HOS 188 124 939 952 13470 12922 13010 T 13402 OBS OBS

3428 No. of Cases 3408 ***** (0) **‡** 9 5 (Ro. Obs) 1.25 0.25 9 1.08 0.54 4 (No. Obs) 0.43 0.57 Blas by Category 3 (No. Obs) 1.32 0.45 2.85 1.15 Contingency Table 2 (No. Obs) 0.95 0.96 (216) 96.0 0.89 (661) 1.00 1.05 1.00 1.00 1 (No. Obs.) Speed Threst Score (>27 Kts) .20 90. .13 90 Percent Fost. Correct 17.4 16.9 91.1 92.1 Table 3.5. Same as Table 3.2 except for 24 stations in the Eastern Region. Skf11 Score .329 .375 .317 .313 Mo. of Cases 9448 577 Mean Alg. Error (Kts) 1:3 1.3 1.3 0.B Mean Abs. Error (Kts) 3.0 2.6 3.0 5.9 No. of Canes 573 1440 Direction Skill Score .560 .362 .525 .421 Abs. Error (Deg) Hean 13 28 32 71 Type of Fcst. Local Local HOS HOS Fcat. Proj. (h) 18 12

* This category was neither forecast nor observed. ** This category was forecast once but was not observed.

No. of Cases 3196 3819 0.00 0.00 0.00 0.00 0.14 0.57 3) 1.75 1.00 Bias by Category ј (No. Obs) 1.33 (21) 1.53 0.48 (105) Contingency Table 1.17 1.13 1.41 0.99 0.98 (3343) 96.0 Speed Threat Score (>27 Kts) 80. 00. .13 Percent Fost. Correct 0.76 82.0 93.5 Table 3.6. Same as Table 3.2 except for 23 stations in the Southern Region. Skill Score .355. .380 .423 707 No. of Cases 1288 470 Mean Alg. Error (Kts) 2.3 8 ___ Mean Abs. Error (Kts) 3.7 3.3 3.3 3.2 No. of Cases 995 1283 Direction Skill Score .570 .431 .542 .442 Hean Abs. Error (Deg) 20 56 22 54 Local Type of Fost. Local HOS HOS Fcst. Proj. (h) 18 12

4448 4482 No. of Cases 0.83 2.00 1.00 0.17 (6) 0.83 0.55 (9) (6) 1.64 4 (No. Obs) 2.67 0.89 1.56 0.41 Bias by Category 0.82 (274) 3 (No. Obs) 1.40 0.89 (62) 1.21 Contingency Table 1.24 (328) 0.00 1.06 2 (Ro. 0bs) 0.98 (4042) 1.01 (3170) 1.00 Speed Threat Score (>27 Kts) .17 . 20 .20 .21 Percent Fest. Correct 88.5 89.3 71.8 71.5 Same as Table 3.2 except for 28 stations in the Central Region. Skill Score .370 604. .380 .355 Cases 2080 No. of 839 Mean Alg. Error (Kts) 2.1 1.6 1.4 9.0 Mean Abs. Error (Kts) 3.5 5.9 3.4 3.2 No. of Cases 833 2077 Direction Skilli Score .578 .608 965. .443 Mean Abs. Error (Deg) 23 19 5 26 Type of Fost. Local Local Table 3.7. HOS HOS Fost. Proj. (h) 18 12

No. of Cases 2895 2891 0.00 6 (No. Obs) * 0 5 (No. Obs) 1.67 0.33 4 (No. Obs) 1.00 1.13 Bias by Category 3 (No. 0bs) 0.79 1.19 Contingency Table 2 (No. 0bs) 1.52 1.02 (126) 1.19 1.00 0.97 0.98 1 (No. Speed Threat Score (>27 Kts) .33 .33 00 Percent Frst. Correct 91.0 81.6 93.1 Same as Table 3.2 except for 18 stations in the Western Region. Skf11 Score .282 .352 .358 No. of Cases 650 362 Mean Alg. Error (Kts) 2.1 Mean Abs. Error (Kts) 3.8 3.4 No. of Cases 643 360 Direction Skill Score .312 .437 165. Mean Abs. Error (Deg) 27 24 38 Type of Fcst. Local NOS HOS Table 3.8. Fest. Proj. (h) 18 12

* This category was neither forecast nor observed.

0.00

0.60

0.50

0.88

0.92

1.02 (2455)

00.

83.1

.328

1.7

4.1

.319

39

Local

No. of Cases 14668 14494 0.50 0.60 1.17 0.00 6 (No. Obs) 5 (No. Obs) 1.25 0.55 0.75 0.59 4 (No. Obs) 1.45 0.91 0.32 (47) Rias by Category 1.09 0.94 (2050) (518) 1.24 0.96 (953) (180) 3 (No. Obs) 1.22 1.14 Comparative verification of MOS guidance and local surface wind forecasts for 94 stations, 1200 GHT cycle. Contingency Table 1.13 1.04 2 (¥6. 0bs) 0.99 0.99 (13305) 0.99 96.0 1 (No. Obs) Speed Threst Score (>27 Kts) . 15 . 19 90. 90. Percent Fost. Correct 88.2 79.9 80.2 89.0 .380 Sk111 Score .378 .276 .321 No. of Cases 2383 1997 Mean Alg. Error (Kts) 2.5 1.2 2.3 ... Hean Abs. Error (Kts) 3.9 3.9 3.1 No. of Cases 2364 4628 Direction Skill Score .475 .425 414. .484 Hean Abs. Error (Deg) 56 25 23 33 Type of Fast. Local Local MOS Table 3.9. HOS Fcst. Proj. (h) 2 18

Table 3.10. Contingency tables for HOS guidance and local surface wind direction forecasts for 94 stations, 1200 GHT cycle.

	11				100	1										18.	18-h Forecasts	Caafe				11
					71											:						
						HOS											MOS					
		-	. ~	٣	4	~	9	7	60	۲				_	2	3 4	5	•		_	80	f ==
	-	232	99	14	•	15	12	41	111	967		-	6	97 23		11	11		-	3 52		227
	7	44	69	89	=	10	10	Ξ	13	236		7	2	25 35	5 37	-	•			_	-	118
	9	6	33	157	12	31	1	13	4	325			_	6 22	2 125	5 52	16	-		~	7	225
OBS	4	4	0	39	231	159	15	11	9	465	,	OBS 4		_	3 39	9 159	111	v 1		~	2	322
	2	4	3	•	108	111	171	38	•	1051		•		m	~	99 6	462	63	16	9	9	621
	9	7	-	7	11	102	266	156	9	246		•		_	•	6	5 61	155	52	2	7 2	281
	7	6	-	-	9	20	121	578	1117	853	**			4	_	e.	3 15	54	172	2 43		295
	•	11	3	-	7	11	30	215	323	959		æ	4	43		5	9	13	83	3 114		275
	H	375	166	290	450	1059	632	1068	588	4628		-	r 180	06 0	0 223	3 310	769 (300	343	3 224		2364
						Local						ī					Local	=				
		-	7	6	4	~	9	1	80	H				_	2	3	٠	9		_	•	H
	-	252	67	6	6	10	21	12	134	964.		_	109	9 23		6	8 15		~	3 4	42 2	227
	~	47	96	99	11	•	•	8	®	236		•	7	24 34	4 37	111 7	-			2	7	118
	•	•	33	151	85	53	6	7	. 01	325		۴٦.	_	8 19	9 108	8 63	3 18	•		3	3 2	225
088	4	2	2	23	222	187	18	80	m	465	;	. OBS 4		4	3 29	9 152	2 117	80	~	4	5	322
	•	3	C	60	78	141	172	33	13	1051		•	,	2	3 10	09 0	0 432	8 8		16	9 6	621
	9	4	0	2	1	129	260	125	1.9	246	,			2	2	, m	09 /	118		15 1	13 2	181
	1	21	-	7	4	24	151	505	145	853		, •	_	60	2	2	8 21	1 42	2 133		79 2	295
	•	72	2	-	S	14	29	157	376	959		2	~	20	9	2	6	9 15		49 132		275
	H	404	190	252	421	1142	999	847	707	4628			r 210	26 0	2 201	1 318	8 677	7 284	4 295	5 287		2364
											-								-			1

Table 3.11. Contingency tables for MOS guidance and local surface wind speed forecasts for 94 stations, 1200 CHT cycle.

3386 No. of Cases 3411 00.00 0.00 0.00 6 (No. Obs) ***** 0 5 (No. Obs) 4.00 4.00 2.00 4 (No. 6.00 Bias by Category 1.60 0.86 0.86 3 (No. Obs) 1.12 Contingency Table 2 (No. Obs) 1.03 1.32 (295) 1.03 1.42 (166) 0.96 0.98 1.00 1 (No. Obs) 66.0 Speed Threat Score (>27 Kts) 1.00 1.00 00. 00. Percent Fcst. Correct 85.2 92.4 6.06 88.5 Same as Table 3.9 except for 24 stations in the Eastern Region. Skill Score .348 . 256 . 298 .271 No. of Cases 997 726 Mean Alg. Error (Kts) 1.9 2.3 2.7 Mean Abs. Error (Kts) 3.4 3.6 3.9 3.1 No. of Cases 461 723 Direction Skill Score .383 .458 419 .417 Abs. Error (Deg) 25 27 32 27 Type of Fast. Local Local Table 3.12. MOS HOS Fcst. Proj. 12 18

* This category was neither forecast nor observed.

No. of Cases 3858 3737 0.00 * (0) 0.00 0.00 0.67 0.33 5 (No. Obs) 4 (No. Obs) 0.83 0.17 (12) 0.90 Bias by Category 3 (No. (bs) 1.14 0.40 0.67 Contingency Table 1.10 1.35 2 (Ro. Obs) 1.30 0.99 1.00 0.98 1 (No. Obs) 0.97 Speed Threat Score (>27 Kts) 81. 00. 00. . 25 Percent Fost. Correct 83.5 89.5 90.3 82.3 Same as Table 3.9 except for 24 stations in the Southern Region. Skilli Score . 382 .392 .310 .303 No. of Cases 265 1102 Hean Alg. Error (Kts) 5.6 8. <u>:</u> 1.7 Mean Abs. Error (Kts) 3.3 2.9 7 3.7 No. of Cases 1099 591 Direction Skill Score 478 492 .429 491 Mean Abs. Error (Deg) 24 7,7 **3**6 30 Type of Fast. Local Local Table 3.13. HOS HOS Fcst. Proj. (h) 12 18

* This category was neither forecast nor observed.

Cases 4525 4546 No. of 1.00 0.75 0.00 1.67 6 (No. Obs) 2.00 2.50 0.80 1.00 5 (No. Obs) 4 (No. Obs) 1.63 0.71 1.05 0.32 Bias by Category 3 (No. 0bs) 1.27 1.17 1.48 1.26 Contingency Table 1.23 (750) 2 (No. Obs) 0.99 1.05 1.34 (382) 0.95 (3562) 0.97 0.99 1 (No. Obs) 0.98 Speed Threat Score (>27 Kts) 00. .15 .25 .08 Percent Fost. Correct 16.8 8.91 86.3 84.7 Same as Table 3.9 except for 28 stations in the Central Region. Skill Score .298 .371 .396 .336 No. of Cases 945 1761 Mean Alg. Error (Kts) 9.1 2.5 2.3 1.7 Mean Abs. Error (Kts) 3.4 3.2 4.0 3.9 No. of Cases 1757 937 Direction Skill Score .472 .492 767. .456 Mean Abs. Error (Deg) 25 29 26 26 Type of Fest. Local Local Table 3.14. MOS NOS Fest.
Proj.
(h) 18 12

No. of Cases 2846 2853 6 (No. Obs) * ô 0.45 ***** © 5 (No. Obs) 0.91 4 (No. Obs) 0.36 0.50 0.17 Biss by Category 0.78 (193) 1.00 1.17 3 (No. Obs) 0.99 Contingency Table 0.77 1.12 0.85 2 (No. Obs) 1.02 1.10 (2055) 1.01 (2598) 0.99 1 (No. 0bs) 0.99 Speed Threat Score (>27 Kts) 10 .07 80. 9 Percent Fost, Correct 87.6 11.7 75.4 88.5 Table 3.15. Same as Table 3.9 except for 18 stations in the Western Region. Sk i l l Score . 364 .380 .310 . 182 No. of Cases 1052 380 Aig. Error (Kts) .3 0.3 2.7 2.5 Mean Abs. Error (Kts) 3.6 3.0 3.9 4.5 No. of Cases 375 1049 Direction Skf111 Score 378 . 293 .357 .402 Mean Abs. Error (Deg) 36 28 26 8 Local Type of Fast. Local MOS HOS Fost. Proj. 12 8

* This category was neither forecast nor observed. ** This category was forecast once but was not observed.

Table 4.1. Definitions of the cloud amount categories used for the local forecasts and observations. The MOS guidance was based on these same categories for opaque amounts only.

Category	Cloud Amount
1	CLR, -SCT -BKN, -OVC, -X
2	SCT
3	BKN
4	ovc, x

Table 4.2. Comparative verification of MOS guidance and local forecasts of four categories of cloud amount (clear, scattered, broken, and overcast) for 92 stations, 0000 GMT cycle.

			Bias by	Categor	7			
Projection (h)	Type of Forecast	1	2	3	4	Percent Correct	Skill Score	Number of Cases
12	MOS Local No. Obs.	0.78 0.88 5131	1.54 1.22 2619	1.27 1.38 1762	0.79 0.83 3607	52.5 64.9	.355 .519	13119
18	MOS Local No. Obs.	0.74 0.73 3747	1.39 1.24 3834	1.17 1.52 2399	0.71 0.63 3223	51.8 51.8	.351 .356	13203
24	MOS Local No. Obs.	0.85 0.82 3997	1.40 1.25 3534	1.15 1.51 2261	0.66 0.62 3346	49.7 47.8	.323	13138

Table 4.3. Same as Table 4.2 except for 24 stations in the Eastern Region.

	Type of Forecast		Bias by	Category				
Projection (h)		1	2	3	4	Percent Correct	Skill Score	Number of Cases
12	MOS Local No. Obs.	0.58 0.75 993	1.76 1.50 487	1.42 1.56 379	0.90 0.82 1146	49.2 59.0	.311	3005
18	MOS Local No. Obs.	0.52 0.78 501	1.29 1.13 899	1.27 1.45 619	0.82 0.72 1022	51.6 50.5	.336	3041
24	MOS Local No. Obs.	0.65 0.80 844	1.66 1.24 645	1.21 1.62 437	0.80 0.76 1075	46.4 45.3	.280 .268	3001

Table 4.4. Same as Table 4.2 except for 24 stations in the Southern Region.

			Bias by	Category				
Projection (h)	Type of Forecast	1	2	3	4	Percent Correct	Skill Score	Number of Cases
12	MOS Local No. Obs.	0.73 0.89 1411	1.68 1.20 867	1.19 1.32 522	0.61 0.78 811	50.7 64.1	.329 .508	3611
18	MOS Local No. Obs.	0.71 0.73 947	1.42 1.26 1245	1.09 1.40 773	0.53 0.44 661	53.7 52.7	.355 .346	3626
24	MOS Local No. Obs.	0.81 0.80 1087	1.53 1.37 1094	1.07 1.39 677	0.44 0.39 753	50.1 46.7	.315	3611

Table 4.5. Same as Table 4.2 except for 28 stations in the Central Region.

	Type of Forecast		Bias by	Category				
Projection (h)		1	2	3	4	Percent Correct	Skill Score	Number of Cases
	MOS	0.77	1.46	1.39	0.80	52.1	.353	
1 -	Local No. Obs.	0.89 1505	1.17 799	1.35 536	0.86 1152	65.9	.534	3992
	MOS	0.70	1.43	1.28	0.70	48.0	.302	
18	Local No. Obs.	0.62 1170	1.35 1130	1.64 668	0.64 1060	48.3	.313	4028
	MOS	0.87	1.30	1.15	0.72	49.5	.320	
24	No. Obs.	0.76 1148	1.25 1147	1.46 700	0.67 1030	47.8	.302	4025

Table 4.6. Same as Table 4.2 except for 16 stations in the Western Region.

Projection (h)	Type of Forecast		Bias by	Category				
		1	2	3	4	Percent Correct	Skill Score	Number of Cases
	MOS	0.99	1.20	1.00	0.83	59.7	.402	
12	Local	0.95	1.06	1.30	0.88	71.5	.582	2511
**	No. Obs.	1222	466	325	498			
	MOS	0.92	1.41	0.95	0.75	55.5	.362	
18	Local	0.84	1.18	1.71	0.67	57.8	.410	2508
	No. Obs.	1129	560	339	480			
	MOS	1.04	1.08	1.22	0.61	53.4	.357	
24	Local	0.91	1.03	1.64	0.55	52.3	.352	2501
	No. Obs.	918	648	447	488			· .

Table 4.7. Comparative verification of MOS guidance and local forecasts of four categories of cloud amount (clear, scattered, broken, and overcast) for 92 stations, 1200 GMT cycle.

	Type of Forecast		Bias by	Category				
Projection (h)		1	2	3	4	Percent Correct	Skill Score	Number of Cases
12	MOS Local No. Obs.	0.91 0.96 3913	1.32 1.06 3446	1.18 1.34 2197	0.65 0.76 3289	52.0 60.8	.354 .474	12845
18	MOS Local No. Obs.	0.91 0.78 6174	1.54 1.60 1993	1.00 1.72 1413	0.83 0.72 3137	55.9 53.6	.356 .347	12717
24	MOS Local No. Obs.	0.92 0.89 4981	1.49 1.37 2562	1.01 1.48 1729	0.75 0.66 3555	51.1 49.8	.325 .316	12827

Table 4.8. Same as Table 4.7 except for 24 stations in the Eastern Region.

			Bias by	Category				
Projection (h)	Type of Forecast	1	2	3	4	Percent Correct	Skill Score	Number of Cases
12	MOS Local No. Obs.	0.73 0.89 857	1.59 1.22 630	1.33 1.45 439	0.73 0.78 1062	49.3 56.5	.323 .414	2988
18	MOS Local No. Obs.	0.84 0.77 1243	1.72 1.73 381	1.10 1.71 312	0.89 0.79 1038	54.0 53.5	.346 .356	2974
24	MOS Local No. Obs.	0.80 0.83 994	1.73 1.56 462	1.13 1.63 378	0.83 0.71 1143	49.9 48.4	.311	2977

Table 4.9. Same as Table 4.7 except for 24 stations in the Southern Region.

Projection (h)			Bias by	Category				
	Type of Forecast	1	2	3	4	Percent Correct	Skill Score	Number of Cases
	MOS	0.92	1.36	1.06	0.54	52.1	.344	·.
1 2	Local	0.96	1.10	1.29	0.66	63.9	.510	3523
12 Local No. Obs.	1	1079	1060	650	734			*
	MOS	0.89	1.70	0.83	0.74	55.3	.324	
18	Local	0.74	1.67	1.63	0.68	51.9	.307	3421
	No. Obs.	1821	606	410	584			
	MOS	0.78	1.70	0.98	0.64	49.5	.307	
24	Local	0.83	1.36	1.52	0.58	48.8	.302	3528
	No. Obs.	1386	845	506	791		1	

Table 4.10. Same as Table 4.7 except for 28 stations in the Central Region.

			Bias by	Category				
Projection (h)	Type of Forecast	1	2	3	4	Percent Correct	Skill Score	Number of Cases
12	MOS Local No. Obs.	1.01 0.96 1059	1.19 1.04 1107	1.12 1.31 669	0.70 0.80 1010	50.4 58.4	.331	3845
18	MOS Local No. Obs.	0.94 0.76 1830	1.48 1.74 556	1.05 1.85 399	0.83 0.71 1046	57.3 53.6	.373	3831
24	MOS Local No. Obs.	1.02 0.95 1387	1.34 1.33 777	1.01 1.39 527	0.73 0.65 1130	49.9 49.0	.310	3821

Table 4.11. Same as Table 4.7 except for 16 stations in the Western Region.

	Type of Forecast		Bias by	Category				
Projection (h)		1	2	3	4	Percent Correct	Skill Score	Number of Cases
	MOS	0.94	1.19	1.31	0.57	57.6	.418	
12	Local	1.04	0.89	1.34	0.76	65.1	.521	2489
i i	No. Obs.	918	649	439	483			
	MOS	0.98	1.23	1.04	0.81	57.1	.348	
18	Local	0.90	1.24	1.67	0.63	55.8	.348	2491
	No. Obs.	1280	450	292	469	; 		
	MOS	1.07	1.12	0.92	0.77	56.5	.344	
24	Local	0.92	1.25	1.40	0.69	54.0	.331	2501
	No. Obs.	1214	478	318	491			

Table 5.1. Definitions of the categories used for verification of persistence, local, and guidance forecasts of ceiling height and visibility.

Category	Ceiling (ft)	Visibility (mi)
1	<400	<1
2		1-2 3/4
3	1000-2900	3-6
4	<u>≥</u> 3000	>6

Table 5.2. Comparative verification of MOS guidance, persistence, and local ceiling height forecasts for 93 stations, 0000 GMT cycle.

		В	ias by	Categor	У			
Projection (h)	Type of Forecast	1	2	3	4	Log Score	Percent Correct	Skill Score
12	MOS Local Persistence No. Obs.	1.34 0.69 0.76 458	0.68 0.72 0.75 591	0.94 1.26 0.91 1213	1.01 1.00 1.03 12200	2.372 1.468 1.481	82.5 87.4 87.9	.359 .547 .533
15	Local Persistence No. Obs.	0.43 1.67 210	0.51 0.81 551	1.08 0.64 1707	1.02 1.05 12075	1.460	83.9 83.9	.427
18	MOS Local Persistence No. Obs.	1.32 0.30 3.85 91	0.90 0.46 1.49 304	0.76 0.98 0.64 1725	1.03 1.02 1.02 12350	1.267 1.136 1.770	85.2 85.2 82.8	.372 .390 .309
24	MOS Local Persistence No. Obs.	1.16 0.29 2.78 126	0.91 0.47 2.00 223	0.73 1.67 1.31 831	1.02 0.97 0.95 13273	0.936 0.966 1.844	90.8 88.2 84.3	.345 .321 .199

Table 5.3. Same as Table 5.2 except for visibility, 0000 GMT cycle.

		Bi	as by (ategor	у			
Projection (h)	Type of Forecast	1	2	3	4	Log Score	Percent Correct	Skill Score
	MOS	0.67	2.15	0.86	1.00	2.539	76.1	.372
12	Local	0.62	0.64	1.12	1.00	1.724	81.9	.518
	Persistence	0.58	0.47	0.70	1.10	1.652	83.1	.485
	No. Obs.	492	411	2452	11094			
	Local	0.36	0.45	0.96	1.03	1.304	84.1	.409
15	Persistence	1.94	0.77	0.86	1.02	1.681	82.5	.367
	No. Obs.	150	250	2021	12114			
	MOS	0.33	2.24	0.98	1.00	1.109	86.7	.361
	Local	0.25	0.35	0.80	1.03	0.915	88.5	.360
18	Persistence	3.27	1.52	1.21	0.96	1.654	83.4	.301
 -2	No. Obs.	89	127	1430	12824			
	MOS	0.51	1.86	1.06	0.99	1.114	87.1	.346
	Local	0.28	0.31	0.79	1.03	0.939	88.8	.314
24	Persistence	2.54	1.39	1.39	0.94	1.756	82.7	.251
- ·	No. Obs.	114	142	1242	12951			

Table 5.4. Same as Table 5.2 except for ceiling height for 94 stations, 1200 GMT cycle.

		В	ias by (Categor	У			
Projection (h)	Type of Forecast	1	2	3	4	Log Score	Percent Correct	Skill Score
12	MOS Local Persistence No. Obs.	0.92 0.52 0.70 122	0.82 0.76 1.11 229	0.81 1.56 1.36 840	1.02 0.97 0.98 13353	0.840 0.674 0.664	91.3 91.6 92.1	.385 .515 .534
15	Local Persistence No. Obs.	0.42 0.50 163	0.69 0.93 275	1.61 1.43 806	0.98 0.98 13435	0.873 0.935	90.2 89.7	.444
18	MOS Local Persistence No. Obs.	1.12 0.35 0.34 255	0.96 0.79 0.81 314	0.83 1.60 1.21 930	1.01 0.97 1.00 12861	1.411 1.204 1.286	88.2 87.8 87.2	.362 .420 .327
24	MOS Local Persistence No. Obs.	1.41 0.37 0.18 479	0.80 0.72 0.43 591	0.85 1.67 0.94 1204	1.01 0.97 1.07 12161	2.554 2.188 2.194	81.5 80.8 81.4	.329 .355 .211

Table 5.5. Same as Table 5.2 except for visibility for 94 stations, 1200 GMT cycle.

		В	las by	Categor	y			
Projection (h)	Type of Forecast	1	2	3	4	Log Score	Percent Correct	Skill Score
12	MOS Local Persistence No. Obs.	0.40 0.41 0.61 109	1.70 0.57 0.89 145	0.98 1.08 1.00 1270	1.00 1.00 1.00 13012	1.021 0.686 0.666	88.1 91.7 92.6	.382 .560 .607
15	Local Persistence No. Obs.	0.58 0.71 90	0.71 1.02 129	1.16 0.99 1281	0.99 1.00 13172	0.817 0.810	89.8 90.6	.473 .489
18	MOS Local Persistence No. Obs.	1.19 0.55 0.46 148	1.71 0.95 0.82 161	0.84 1.25 0.88 1412	1.01 0.98 1.02 12634	1.308 1.168 1.080	86.7 86.4 88.1	.371 .410 .403
24	MOS Local Persistence No. Obs.	0.90 0.38 0.13 506	1.98 0.80 0.30 432	0.87 1.14 0.51 2442	1.00 1.00 1.18 11038	2.764 2.416 2.430	75.6 76.5 77.2	.372 .378 .232

Table 6.1. Verification of MOS guidance and local max/min temperature forecasts for 93 stations, 0000 GMT cycle.

Forecast Projection	Forecast Type	Number of Cases	Mean Algebraic Error (°F)	Mean Absolute Error (°F)	Percent of Absolute Errors >10°F	Probability of Detection (32°F)	False Alarm Ratio (32°F)
Today's	MOS		1.1	3.1	2.8	:	ı
Мах	Local	14597	0.7	2.9	2.2	1	1
Tonight's	MOS		-0.8	3.3	2.0	0.40	99.0
Min	Local	14598	-0.4	3.1	1.6	0.34	0.55
Tomorrow's	MOS		0.7	3.8	4.9	:	;
Мах	Local	14571	9.0	3.7	4.7	1	1
Tomorrow	MOS		-1.1	3.9	4.6	0.35	0.73
Night's Min	Local	14564	8.0-	3.8	4.0	0.30	0.64

Same as Table 6.1 except for 24 stations in the Eastern Region. Table 6.2.

Forecast Projection	Forecast Type	Number of Cases	Mean Algebraic Error (°F)	Hean Absolute Error (°F)	Percent of Absolute Errors >10°F	Probability of Detection (32°F)	False Alarm Ratio (32°F)
Today's	MOS	2362	1.1	3.3	3.3		
×	Local	7656	0.0	3.1	3.1	i i	!
Tonight's	HOS		-0.7	3.2	2.0	0.18	0.86
Min	Local	3373	-0.1	3.0	1.6	0.12	0.83
Tomorrow's	MOS		1.0	3.9	5.0	t I	1
Мах	Local	3335	9.0	3.8	6.4	;	1 1
Tomorrow	MOS		-1.0	3.8	3.7	0.25	0.83
Night's Min	Local	3362	9.0-	3.7	3.4	0.25	0.78

Same as Table 6.1 except for 24 stations in the Southern Region. Table 6.3.

Projection	rorecast Type	Number of Cases	Mean Algebraic Error (°F)	Mean Absolute Error (°F)	Percent of Absolute Errors >10°F	Probability of Detection (32°F)	False Alarm Ratio (32°F)
Today's	MOS		1.2	2.8	2.0		1
Мах	Local	3951	0.8	2.5	1.6	ţ	;
Tonight's	MOS		-0.0	2.9	1.3	0.00	*
Min	Local	3939	0.1	2.8	6.0	0.00	*
Tomorrow's	МОЅ		9.0	3.2	3.0	i i	i i
Мах	Local	3953	8.0	. 3.1	3.1	t 1	!
Tomorrow	HOS		-0.2	3.4	2.8	0.00	*
Night's Min	Local	3928	-0.1	3.4	3.1	0.00	*

*No forecasts of <32°F were made.

Same as Table 6.1 except for 28 stations in the Central Region. Table 6.4.

Forecast Projection	Forecast Type	Number of Cases	Mean Algebraic Error (°F)	Mean Absolute Error (°F)	Percent of Absolute Errors >10°F	Probability of Detection (32°F)	False Alarm Ratio (32°F)
Today's Max	MOS Local	4553	1.0	3.3	3.1	# 1 # #	!!
Tonight's Min	MOS Local	4550	-0.9	 	2.1	0.47	0.56
Tomorrow's Max	MOS Local	4545	0.7	4.0	5.9	11	1 1
Tomorrow Night's Min	MOS Local	4542	-1.1	4.3	5.8	0.37	0.69

Same as Table 6.1 except for 17 stations in the Western Region. Table 6.5.

Forecast Projection	Forecast Type	Number of Cases	Mean Algebraic Error (°F)	Mean Absolute Error (°F)	Percent of Absolute Errors >10°F	Probability of Detection (32°F)	False Alarm Ratio (32°F)
Today's Max	MOS Local	2741	1.0	3.1	2.8	4 4	
Tonight's Min	MOS Local	2736	-2.1	3.6	2.8 2.6	0.56	0.61
Tomorrow's Max	MOS Local	2738	0.6	3.8	5.8 4.2	:] : :	; ; ; ;
Tomorrow Night's Min	MOS Local	2732	-2.6	4.2	5.8	0.47	0.69

Table 6.6. Verification of MOS guidance and local max/min temperature forecasts for 93 stations, 1200 GMT cycle.

Forecast Projection	Forecast Type	Number of Cases	Mean Algebraic Error (°F)	Mean Absolute Error (°F)	Percent of Absolute Errors >10°F	Probability of Detection (32°F)	False Alarm Ratio (32°F)
Tonight's Min	MOS Local	14536	-1.1	3.1	1.2	0.50	0.58
Tomorrow's Max	MOS Local	14539	1.1	3.7	4.7	: 1	: :
Tomorrow Night's Min	MOS Local	14548	-0.9 -0.6	3.7	3.1	0.36	0.76
Day After Tomorrow's Max	MOS Local	14486	1.2	4.3	7.2	1 1	1 1

Same as Table 6.6 except for 24 stations in the Eastern Region. Table 6.7.

Forecast Projection	Forecast Type	Number of Cases	Mean Algebraic Error (°F)	Mean Absolute Error (°F)	Percent of Absolute Errors >10°F	Probability of Detection (32°F)	False Alarm Ratio (32°F)
Tonight's Min	MOS Local	3332	-0.9 -0.5	2.9	0.9	0.25 0.25	0.79
Tomorrow's Max	MOS Local	3316	1.3 0.8	3.8	5.2	1 1	; ! ; ;
Tomorrow Night's Min	MOS Local	3335	-0.9	3.6 3.4	2.5	0.21 0.29	0.90
Day After Tomorrow's Max	MOS Local	3290	1.3	4.3	6.9 7.1	1 1	; ;

Same as Table 6.6 except for 24 stations in the Southern Region. Table 6.8.

Forecast Projection	Forecast Type	Number of Cases	Mean Algebraic Error (°F)	Mean Absolute Error (°F)	Percent of Absolute Errors >10°F	Probability of Detection (32°F)	False Alarm Ratio (32°F)
Tonight's Min	MOS Local	3898	-0.5	2.7	9.0	00.00	1.00
Tomorrow's Max	MOS Local	3912	0.8	3.2	3.3	1 1 1 1	: :
Tomorrow Night's Min	MOS Local	3901	-0.2	3.1	2.5	0.00	1.00
Day After Tomorrow's Max	MOS Local	3906	0.6 0.8	3.6	4.7	; ;	; ;

*No forecasts of $\leq 32^{\circ}F$ were made.

Table 6.9. Same as Table 6.6 except for 28 stations in the Central Region.

Forecast Projection	Forecast Type	Number of Cases	Hean Algebraic Error (°F)	Mean Absolute Error (°F)	Percent of Absolute Errors >10°F	Probability of Detection (32°F)	False Alarm Ratio (32°F)
Tonight's Min	MOS Local	4574	-1.2	3.3	1.4	0.63	0.53
Tomorrow's Max	MOS Local	4571	1.3	3.6	5.6	1 1	: 1
Tomorrow Night's Min	MOS Local	4575	-0.3	3.8	3.6	0.41 0.25	0.74
Day After Tomorrow's Max	MOS Local	4568	1.4	4.6	8.7	: 1	! !

Table 6.10. Same as Table 6.6 except for 17 stations in the Western Region.

Forecast Projection	Forecast Type	Number of Cases	Mean Algebraic Error (°F)	Mean Absolute Error (°F)	Percent of Absolute Errors >10°F	Probability of Detection (32°F)	False Alarm Ratio (32°F)
Tonight's Min	MOS Local	2732	-2.3	3.8	2.3	09.0	0.47
Tomorrow's Max	MOS Local	2740	1.1	3.00	4.5	i 1	; ;
Tomorrow Night's Min	MOS Local	2737	-2.2	3.9	4.0 3.6	0.50	0.62
Day After Tomorrow's Max	MOS Local	2722	1.3	4.6	7.3	: :	! ;